

0340 CENTER HUNG TOP PIVOT

1/4-20 X 5/8" FHMS
OR
#14 X 1-1/2" FHWS

1-5/16" 2 1/32"

6-3/4" 6" JAMB PORTION

15/32"

Ø7/8"

1-15/32"

9/32"

12-24 X 5/8" FHMS
OR
#12 X 1-1/4" FHWS
(2 PLACES)

9/32"

9/16"

1-7/16"

1/4"

1/16"

3/4"

HEEL EDGE OF DOOR
SEE NOTE 2 1/8"

Ø1"

R5/8"

DOOR PORTION

1-1/8"

4-13/16"

5-9/32"

5/8"

1-1/4"

1/4-20 X 5/8" FHMS
OR
#14 X 1-1/2" FHWS
(2 PLACES)

NOTES:

1. REINFORCING BY OTHERS.
2. RADIUS HEEL EDGE OF DOOR 1-1/4" MAX FOR 1-3/8" - 2-1/2" THICK DOORS
3. IT IS THE DOOR AND FRAME MANUFACTURERS RESPONSIBILITY TO CHECK THE HARDWARE SCHEDULE AND PREP THE DOORS AND FRAMES.
4. CENTERLINE OF TOP PIVOT PIN MUST BE PLUMB AND STRAIGHT WITH BOTTOM PIVOT OR CLOSER SPINDLE.

DRESS PLATE

PIVOT PIN SHOWN EXTENDED

TO BE DETERMINED BY
BOTTOM PIVOT OR CLOSER

DO NOT SCALE DRAWING

0340 CENTER HUNG TOP PIVOT

1/4-20 X 5/8" FHMS
OR
#14 X 1-1/2" FHWS

1-5/16" 2 1/32"

6-3/4" 6" JAMB PORTION

15/32"

Ø7/8"

1-15/32"

9/32"

12-24 X 5/8" FHMS
OR
#12 X 1-1/4" FHWS
(2 PLACES)

9/16" 1-7/16"

9/32"

1/4" 1/16"

3/4"

HEEL EDGE OF DOOR
SEE NOTE 2 1/8"

Ø1"

R5/8"

DOOR PORTION

1-1/8"

4-13/16"

5-9/32"

5/8" 1-1/4"

1/4-20 X 5/8" FHMS
OR
#14 X 1-1/2" FHWS
(2 PLACES)

NOTES:

1. REINFORCING BY OTHERS.
2. RADIUS HEEL EDGE OF DOOR 1-1/4" MAX FOR 1-3/8" - 2-1/2" THICK DOORS
3. IT IS THE DOOR AND FRAME MANUFACTURERS RESPONSIBILITY TO CHECK THE HARDWARE SCHEDULE AND PREP THE DOORS AND FRAMES.
4. CENTERLINE OF TOP PIVOT PIN MUST BE PLUMB AND STRAIGHT WITH BOTTOM PIVOT OR CLOSER SPINDLE.

DRESS PLATE

PIVOT PIN SHOWN EXTENDED

TO BE DETERMINED BY
BOTTOM PIVOT OR CLOSER

DO NOT SCALE DRAWING